

EURO PLASTiK

To All World

**LIGHT SERIES HALOGEN FREE COIL PIPES
TECHNICAL DATA SHEET**



SPECIFICATIONS

- Compression Resistance: 320N
- Impact Resistance: 2 kg.
- Min. Operation Temperatur: – 15°C
- Max. Operation Temperature +60°C



SIZES

SIZE	Inside mm Ø	Outside mm Ø	Packing (mt.)
14	11	14	100
16	13	16	250
18	15	18	200
20	16,6	20	150
25	20,8	25	100
32	26,4	32	100
40	34	40	100
50	43,6	50	100
63	56	63	50



USAGE AREAS

They are being used in all buildings where there is not much external pressure, where there are mechanical stresses, in buildings, dwellings, prefabricated buildings, in all applications under mortar and upon mortar, inside concrete, sheetrock, walls or in suspended ceilings, and in all buildings where the formation of halogen, acid gas is undesirable. In case of burning out, the gas extrusion does not adversely affect the human health. They are resistant to breakage, smashing and impacts.

Due to the fact that they are being produced as coils and at the same time as air-operated production, they provide many advantages such as convenience in cabling, labor saving and minimum usage of articulation components. They are being produced in accordance with TS EN 61386-22 standard.

